



**KÖSTER**

## KÖSTER Restoration Plasters

KÖSTER Restoration Plasters are especially designed for the restoration of masonry with high salt and moisture contents. They are very tough yet have a high air pore volume. They are also not affected by high salt contents and prevent salts from diffusing to the surface. When rising damp is stopped with KÖSTER Crisin 76, KÖSTER Restoration Plasters help to dry out the wall and absorb remaining salts. KÖSTER Restoration Plasters are available in grey or white. In historic buildings they can be used as a decorative plaster even without painting. They are suitable for interior and exterior use and comply with the harmonized european Norm (CE).



Priming with  
KÖSTER Polysil TG 500



Application of a plaster key made  
of KÖSTER Restoration Plaster



Application of  
KÖSTER Restoration Plaster



Floating the surface

## KÖSTER at your service – worldwide.



### // Contact us

KÖSTER BAUCHEMIE AG  
Dieselstraße 1–10 · 26607 Aurich  
Tel.: +49 4941 9709 0  
E-Mail: [info@koster.eu](mailto:info@koster.eu)  
[www.koster.eu](http://www.koster.eu)

Follow us on social media:



Issued: 1/2022

**KÖSTER**

Waterproofing Systems

## KÖSTER KD System

Quick system for basement waterproofing



Waterproofing in seconds!

Against pressing water



## // Sealing active leaks with KÖSTER KD 2 Blitz powder:



1 Active leaks...



2 ...stopped...



3 ...in seconds!

KÖSTER KD 2 Blitz Powder is a highly reactive powder with an extremely short setting time. It stops flowing water within seconds. Form the powder into a firm ball and press it onto the leakage.

## // Surface waterproofing with the KÖSTER KD System:



1 KÖSTER KD 1 Base



2 KÖSTER KD 2 Blitz Powder



3 KÖSTER KD 3 Sealer



4 KÖSTER KD 1 Base:  
in 2 coats (second layer  
after 30 minutes)

After stopping the leakage the surrounding area is waterproofed: Mix as much KÖSTER KD 1 Base as can be applied within 10 minutes into a viscous, spreadable mass (slurry). The slurry should have a creamy, easy to brush consistency. Apply using a firm brush. Immediately rub KÖSTER KD 2 Blitz

Powder into the fresh, moist slurry with a gloved hand until the surface is dry. Without waiting, brush on the KÖSTER KD 3 Sealer with a clean brush. Immediately afterwards and again after approx. 30 minutes, repeat step 1 (KÖSTER KD 1 Base). The maximum total thickness should be less than 4 mm.

## Key features of the KÖSTER KD System

- Surface waterproofing against pressurized water from the negative side
- No external excavation necessary
- KÖSTER KD 2 Blitz Powder seals active leaks in seconds.
- Penetrates deeply into the substrate and blocks the pores
- Resistant to salts which are harmful to the building structure
- Salts will not detach the fully cured KÖSTER KD System coating from the substrate.
- Easy to apply
- Also suited for positive side waterproofing
- Decades of well-proven experience

**The perfect solution for small  
repair works in the basement:**  
The KÖSTER KD System in one package!

- 7.5 kg KÖSTER KD 1 Base
- 7.5 kg KÖSTER KD 2 Blitz Powder
- 3 kg KÖSTER KD 3 Sealer



Enough material to  
cover approximately  
5 m<sup>2</sup>.